

# Hebeschiebe

- Uygulama alanında en az 20 cm duvar kalınlığına ihtiyaç vardır.
- Bir kanat için taşıma kapasitesi 300 kg olup, yatay 3000 mm, dikey 2765 mm ye kadar kanat yapılabilir.
- Özel tasarlanmış taşıyıcı araba sayesinde son derece sessiz ve kolay çalışır ve istenilen noktada kanat sabitlenebilir.
- 4 kanatlı bir sistemde 12000 mm kadar genişlikteki alanlarda uygulanabilir.

- At least 20 cm wall thickness is needed in the application area.
- For a sash, the carrying capacity is 300 kg and it can be made up to 3000 mm horizontal and up to 2765 mm vertical.
- It is very quiet and easy to operate thanks to the specially designed carriage and the wing can be fixed at the desired point.
- It can be applied in areas with a width of 12000 mm in a system with 4 blades.



24,32,42 mm cam kalınlıkları  
24,32,42 mm glass thickness



Estetik görümlü çift cam çitisi  
Aesthetic appearance double glazing bead



Isı, ses, toz ve suyu absorbe eden özel conta  
Special gasket that absorb heat, noise, dust and water



ECOLOGY  
CONCEPT

**80mm**  
**KANAT**  
**SASH**

**185mm**  
**Kasa**  
**FRAME**



Destek sacı  
Reinforcement steel



Hebeschiebe

Daha Geniř,  
Daha Ferah  
Manzara  
isteyenlere

For those  
who want a  
wider, more  
spacious view

 **Pidosan**  
KAPI - PENCERE



